

Technical Data Sheet



Reaction time
approx. 15 min.



Consumption
40 ml per 1 L



Application field
for use in all automatic
transmission with
torque converter



Application interval
before every change of
transmission oil

Automatic Transmission Cleaner



Application

1) Add to automatic gear box before exchanging the transmission fluid.
2) Run engine approx. 15 min with frequent load changes (use all gear positions). 3) Exchange transmission fluid and filter according to manufacturer's instructions.

Sufficient for up to 8 L capacity. For larger capacities add 40 ml per liter of gear oil.

Description

GAT Automatic Transmission Cleaner is a high performance cleaner for all types of automatic transmissions.

Advantages

Removes operationally caused contamination and deposits from the automatic transmission gear box. Protects against corrosion and premature wear. The optimum shift function is restored and the service life of the automatic transmission is increased.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62023
1 L	12 x 1 L	Art. 62050
5 L	–	Art. 62051
200 L	–	Art. 62223

other sizes available on request

Properties

Physical state	liquid
Color	light yellow
Density	0,80 g/cm ³ DIN 12185
Flash point	61 °C ISO 3679
Viscosity	1,5-2,5 mm ² /s DIN EN ISO 3104 (@ 40 °C)

Compatibility

Mixable with all types of automatic transmission fluids.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.