

Technical Data Sheet



LPG Valve Protect



Reaction time
works during operation



Application field
for use in all LPG engines with
(automatic or manual) valve
protection dosing feed system



Consumption
50 ml per 50 L



Application interval
with every tank filling

Application

For application in vehicles with bivalent engines and automatic or mechanical dosage system. 50 ml sufficient for 50 L of fuel, the product will be automatically diluted. Product works during operation.

Description

GAT LPG Valve Protect is a highly efficient additive for dosage systems that considerably reduces wear and tear of valves and valve seats of liquefied petroleum gas (LPG) powered engines. Reliably and lastingly removes even smallest particles of contamination in the entire combustion system.

Advantages

Long-term protection of valves and valve seats due to permanent lubrication of the valves. Optimized fuel consumption and reduced exhaust gas emission. Protects against valve impact and extends the life span of the engine.

Packing sizes	Packing Unit	Article Number
---------------	--------------	----------------

1 L	12 x 1 L	Art. 62039
-----	----------	------------

other sizes available on request

Properties

Physical state	liquid
Colour	colourless - light yellow
Density	0,80 g/cm ³
Flash point	>61 °C
Viscosity	1,0-2,5 mm ² /s (at 20 °C)

Compatibility

For application in vehicles with bivalent engines and automatic dosage system.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.