

Technical Data Sheet



Reaction time
works during operation



Consumption
60 ml for 1 liter



Application field
for use in all diesel and gasoline engines



Application interval
with every oil change or on demand

Hydraulic Lifter Care & Protect



Application

Add to the warm engine oil after every oil change or when required. Works during operation. Sufficient to treat 5 L of engine oil. For larger volumes add 60 ml product per liter engine oil. Compatible with all mineral and synthetic engine oils.

Attention: Check engine oil level before application! We recommend cleaning of the oil system with Engine Cleaners before application.

Description

GAT Hydraulic Lifter Care & Protect contains a high performance package of effective additives for improved high pressure properties as well as wear and tear protection of all types of engine oils.

Advantages

Only a well-functioning engine can run on full power! Disturbing rattle sounds will be eliminated. Reduction of wear and tear due to optimized lubrication.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62042
1 L	–	Art. 62156

other sizes available on request

Properties

Physical state	viscous
Color	yellow - amber
Density	0,9 g/cm ³
Flash point	>100 °C
Viscosity	>20 mm ² /s (@ 40 °C)

Compatibility

Compatible with all mineral and synthetic engine oils.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.