

# Technical Data Sheet



**Reaction time**  
works during operation



**Consumption**  
50 ml per 10 L



**Application field**  
for use in all diesel and gasoline engines



**Application interval**  
with every tank filling or on demand

## CAT Clean Catalytic Converter & Oxygen Sensor Cleaner



### Application

Recommended to add with every tank filling to the tank before filling up. Product works during operation, sufficient for up to 60-80 L petrol. For larger tank volumes add 50 ml per 10 L of the filling content.

### Description

GAT CAT Clean cleans the entire fuel system thanks to the latest additive technology. It dissolves resinification in the fuel system as well as gummy carbon deposits on lambda probes and catalytic converters. Suitable for petrol and diesel engines.

### Advantages

Prevents heavy contamination, if it is used regularly, optimizes fuel efficiency and engine performance, supports the proper function of the catalytic converter and oxygen sensor. Expensive workshop visits or breakdowns can thus be avoided.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62073
1 L	12 x 1 L	Art. 62134
10 L	-	Art. 62119

other sizes available on request

### Properties

Physical state	liquid
Color	colourless
Density	0,88 g/cm <sup>3</sup>
Flash point	>61 °C
Viscosity	<7 mPa·s (at 40 °C)

### Compatibility

Recommended for use in all diesel and gasoline engines.

### Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

### Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.