

# Technical Data Sheet



**Reaction time**  
approx. 15 min.



**Application field**  
for use in all water cooled,  
closed cooling systems



**Consumption**  
2 x 175 ml for up to 10 L



**Application interval**  
with every coolant change

## Radiator Oil Cleaner C2



### Application

1) Shake both cans well before use! 2) Add the complete content of both cans (component 1 and 2) into the cooling system. 3) Turn the temperature regulator on "warm" and let the engine run for approx. 15 minutes at midrange speed to reach the optimal operation temperature. Make sure that the complete cooling circuit is used to ensure that the cooling system will completely cleaned. 4) Drain the coolant afterwards. 5) Afterwards rinse the entire cooling system thoroughly with clear water. 6) Refill the system with coolant according to the manufacturer's instructions. The product-system is sufficient to treat cooling systems of 5 to 10 liters capacity.

### Description

**GAT Radiator Oil Cleaner C2** for use in all water cooled, closed cooling systems (commercial vehicles, passenger cars, industrial heat exchangers). Contains quick-reacting components for removal of oily deposits caused by defect cylinder head gaskets or leaking radiators and effectively cleans the entire cooling system. Dissolves other operationally caused contamination, e. g. scale, coolant sludge, lime and fur deposits and cleans water coolers, boilers and heat exchangers. Valves, thermostats and water pumps return to there optimal performance.

### Advantages

The major part of chemical energy that is bound in the fuel is converted into heat during the combustion process which must be dissipated. Therefore a fully functional cooling system is of major importance for the operational liability of engines! Improved heating and cooling performance. Increases the operational liability of the cooling system and extends the life span of all aggregates.

### Properties

Physical state	liquid
Color	colourless
Density	0,82 g/cm <sup>3</sup> DIN 12185
Flash point	-9 °C ISO 3679
Viscosity	0,73 mm <sup>2</sup> /s DIN EN ISO 3104 (at 40 °C)

### Compatibility

Compatible with all water-cooled, closed cooling systems (commercial vehicles, cars, other industrial heat exchangers).

### Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

### Disposal

Dispose of this product and container according to national/ regional regulations.

Packing sizes	Packing Unit	Article Number
175 ml	Set 2x175 ml	Art. 62132
other sizes available on request		

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.