

Technical Data Sheet



Reaction time
works during application



Consumption
depending on application



Application field
for all kind of engines



Application interval
on demand

Injector Dismantling Aid

Application

Shake the product well before use. Remove soilings roughly and afterwards spray affected connection generously. Let the product affect approx. 10-15 min.

Description

GAT Injector Dismantling Aid contains selected raw materials for a fast and effective release of stuck components such as injectors, spark plugs and glow plugs. Due to a strong material cooling, deposits are dissolved. The included special lubricating components ensure a simple and gentle disassembly afterwards.

Advantages

Easy and quick application. Stuck connections are effectively dissolved. Due to special lubricants, "ripping off" is prevented. Ideal for maintenance.

Packing sizes	Packing Unit	Article Number
400 ml	24 x 400 ml	Art. 62164

other sizes available on request

Properties

Physical state	liquid, aerosol
Color	translucent
Density	0,641 g/cm ³
Flash point	< 0 (not applicable) °C

Compatibility

Applicable on all metal surfaces. Before the application on painted surfaces, rubber or plastic material compatibility has to be checked.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.